

Technical data

Feature	Specification / options	Notes
Safe working load (SWL) under the spreader	Single 41t / Twin 50t*/ Twin 60t*/ Twin 65t*	*Check availability from your Kalmar contact
Gantry rail span	Up to 11 wide	-
Hoisting height	Up to 1 over 6	-
Rope reeving	8-rope stiff reeving	-
Overall length (buffer to buffer)	14,5m 47ft 7in	Buffers uncompressed, varied as required
Main power supply	50 or 60Hz, 3-phase, 4-wire, voltage as required	Typical voltage: 10-20kV Typical transformer size: 630-800kVA
Power supply method	Cable reel	-
Electrical and automation system supplier	Kalmar	-
Intelligent features	Fully automated operation Yard automation including Kalmar Automatic Truck Handling Kalmar Key Kalmar Insight	-

Baseline in bold

Metric units primary

Spreader options	ISO containers	Pallet wides	Trailers & Swap bodies	North America WTP containers (48ft, 53ft)	Notes
Bromma - fully electric	Х	X*	-	-	-
Bromma Twin - hydraulic	X (also twin)	X*	-	-	Check availability from your Kalmar contact

Baseline in bold

*Optional feature

Trim and micro motion options	Range	Options
Trim	±5°	No trim / electric
Micro motions (headblock)	±250mm / ±250mm / ±5° ±10in / ±10in / ±5°	Electric / hydraulic

Baseline in bold Metric units primary

Typical performance values	Speed options	Acceleration / Deceleration
Hoisting with SWL under spreader	35 / 45m/min 114 / 147ft/min	0.35 m/s ²
Hoisting with empty spreader	70 / 90m/min 229 / 295ft/min	0.50 m/s ²
Trolley travel	60 / 72m/min 197 / 236ft/min	0,30m/s²
Gantry travel	240 / 270 / 300m/min 9 / 10 / 11mph	0,40m/s²

Baseline in bold

Metric units primary

Design classifications (F.E.M)

Crane classification	U8/Q3/A8 4 million container moves
Hoist mechanism	T8/L2/M8
Trolley traversing mechanism	T7/L3/M8
Gantry travelling mechanism	T8/L3/M8

Classifications varied as required

Baseline







Published by Kalmar, part of Cargotec. Copyright © Cargotec 2018. All rights reserved. No part of this publication may be copied or reproduced without permission of the copyright owner. The content of this document is provided "as is", without warranties of any kind with regards to its accuracy or reliability and excluding all implied warranties. We reserve the rights to make changes to any of the items described in this document without prior notice. The content of each service and availability of particular services may vary.

www.kalmarglobal.com